

CODE	FDP09-AE	ARTICLE NAME	0.15mm Flame Retardant Double-Sided Tape
PRODUCT CONSTRUCTION			
***** *****		Flame Retardant Acrylic Adhesive	
		Non-woven	
//////////////////////////////////// ////////////////////////////////////		FabricFlame Retardant Acrylic Adhesive	
***** *****		Double PE Release Liner	
SUBSTRATE		LINER	
ARTICLE NAME	Non-woven Fabric	ARTICLE NAME	Double PE Release Liner
COLOR	White	COLOR	White
PRINTABILITY	NO	SMOOTHNESS	GOOD
DIE CUTTING PRESSURE-SENSITIVE ADHESIVE	GOOD		
ADHESIVE	Acrylic Adhesive	INITIAL TACK (NO/BALL) 1	1st side 5# ↑ 2nd side 5# ↑
TOTAL THICKNESS (mm)	0.15 ± 0.005	180° PEELING ADHESIVE (kg/25mm)	1st side 1.8 ↑ 2nd side 1.8 ↑
HEAT RESISTANT	100°C*30min	HOLDING STRENGTH 80°C (hr/kg*25mm)	1st side 48 ↑ 2nd side 48 ↑
SOLVENT RESISTANCE	Normal	TEMPERATURE & HUMIDITY RANGE	-10~85°C / 0~95%RH
WEATHER RESISTANCE	Normal	FIRE-PROTECTION RATING	UL94-VTMO
SHELF LIFE	6 months from date of despatch by JORN when stored in the		

CODE	FDP09-AE	ARTICLE NAME	0.15mm Flame Retardant Double-Sided Tape
	original carton at 21° C (70° F) & 50% Relative Humidity		
REMARK	THE TECHNICAL DATA ARE BASED ON RELIABLE TESTS CONDUCTED BY THE COMPANY. HOWEVER, THE COMPANY DOES NOT GUARANTEE ALL PROPERTIES AND CHARACTERISTICS ARE FULLY IN ACCORDANCE WITH THE SPECIFICATION. PLEASE VERIFY THE SUITABILITY OF THE PRODUCT FOR YOUR INTENDED USE AND CONDITIONS BEFORE APPLICATION, OR CONTACT US FOR FURTHER INFORMATION AND SERVICE.		
ISSUE DATE	2023/06	REVISION DATE	
VERSION	A		